

Single Check Valves

Single check valves are used in fire protection systems to allow waterflow in one direction only. Typical applications are at connections between public water supplies and private fire service systems, at the discharge from fire pumps, at gravity tank connections and at fire service pumper connections.

Valves identified in the listing by a single asterisk (*) have side covers; valves identified by a double asterisk (**) have no removable covers; others have top covers. Clearance must be provided for side-cover valves to permit clapper removal. Valves without covers must be removed from the system for clapper replacement or repair. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Model MGCV

<i>Product Designation</i>	<i>Description</i>	<i>Nominal Pipe Size</i>	<i>Max Working Pressure, psi (kPa)</i>	<i>Remarks</i>
Model MGCV	Swing Check Valve Cut Groove	2, 2 1/2, 3, 4, 6 inch 76.1, 165.1 mm	300 (2070)	a

Remarks

a.) For use in horizontal and vertical installations

Company Name:	Masteco Industry Co Ltd
Company Address:	715-12 (146-Block, 13 Lot) Gojan-Dong, Namdong-Gu, Incheon, South Korea
Company Website:	http://www.masteco.co.kr
New/Updated Product Listing:	No
Listing Country:	South Korea
Certification Type:	FM Approved